

Alpine FRESH

M3 Series Specification Sheet

Water Reservoir

- Fabricated from seamless hard drawn copper and tin plated for your safety
- 1.5L Capacity
- Chilling Capacity of 10L per hour

Refrigeration

- Uses 250gms of refrigerant R134A which is non-toxic, non-flammable and environmentally friendly
- Refrigerant flow is controlled by a capillary tube which has no moving parts
- To give maximum heat exchange a suction line is fitted

Water Flow Controls

- The bubbler is rated to supply 1.7L per min at mains water pressure of between 140 and 700kPa
- An automatic, self-regulating control is fitted to overcome varying mains pressure

Water Connections

- Water inlet – ½" male B.S.P.
- Water outlet – 40mm female F.P.V.C pipe

Thermostat Control

- The thermostat is factory pre-set

Compressors

- 1/8 hp capacity
- 138 Watts
- Hermetically sealed for silent running

Condenser

- Copper tube and expanded aluminium tin

Electrical

- 240 volts, 50 Hz
- 2m house cable and 3 pin plug is supplied

Performance to ARI 1010-94 Standard

- Inlet water – 26.7°C
- Outlet water - 10°C
- Ambient air – 32.2°C

Weight – Packed

- 26kgs

Dimensions

- Width – 350mm
- Depth – 350mm
- Height - 1100mm

